

TV SYNT PELLETT 840



- N° 1 steamer for each deck
- Hood with one speed exhaust fan
- N° 1 steam exhaust valve each deck
- Baking plates in "armored concrete"
- Dismountable glass doors and with lever opening
- Safety thermostat
- Steam generators control by electrovalve with timer
- Presetting for shipment of oven fully assembled
- Automatic start
- Aided draught kit
- Available in versions SMART 0.8H and 0.20H, and HI CONTROL 0.20H depending on working hours

<i>Power inlet</i>	400/3N~/50
<i>Water inlet</i>	Ø ½" GAS
<i>Steamer drain</i>	Ø 1" GAS
<i>Fuel pipe inlet</i>	-----
<i>Steam exhaust output</i>	Ø 150 mm
<i>Fume exhaust output</i>	Ø 200 mm
<i>Frontal door (anti-explosion and clearing access)</i>	Pos.1
<i>Inspection rear flue cleaning</i>	Pos.2
<i>Side rear cleaning door (Optional burner flame horizontal)</i>	Pos.3

	Chambers	Baking Surface	Dim.	Useful dimension chambers						Installed power		Minimum door width	Weight
				Length	Height					Thermic	Electrical		
					P mm	1°mm	2°mm	3°mm	4°mm				
n°	mq	B mm	P mm	1°mm	2°mm	3°mm	4°mm	5°mm	kcal/h	kW	mm	kg	
3,2 / 84x126-3	3	3,2	1910	1260	200	200	250	-	-	32.000		650x1850	1.900
4,2 / 84x126-4	4	4,2	1910	1260	200	200	200	250	-	32.000		650x2000	2.200
5,3 / 84x126-5	5	5,3	1910	1260	170	170	170	170	250	35.000		650x2100	2.500
4,3 / 84x170-3	3	4,3	2350	1700	200	200	250	-	-	35.000		650x1850	2.500
5,7 / 84x170-4	4	5,7	2350	1700	200	200	200	250	-	40.000		650x2000	2.800
7,1 / 84x170-5	5	7,1	2350	1700	170	170	170	170	250	48.000		650x2100	3.100
5,4 / 84x214-3	3	5,4	2790	2140	200	200	250	-	-	40.000	2,0	650x1850	3.000
7,2 / 84x214-4	4	7,2	2790	2140	200	200	200	250	-	56.000		650x2000	3.400
9,0 / 84x214-5	5	9,0	2790	2140	170	170	170	170	250	60.000		650x2100	3.800
6,5 / 84x258-3	3	6,5	3230	2580	200	200	250	-	-	56.000		650x1850	3.550
8,7 / 84x258-4	4	8,7	3230	2580	200	200	200	250	-	60.000		650x2000	4.000
10,8 / 84x258-5	5	10,8	3230	2580	170	170	170	170	250	65.000		650x2100	4.450

